


FleXbus Aluminum Perforated Profile

Data Solutions

KATALOGNUMMER

FLEXALPROF2M



CERTIFICERINGER



FUNKTIONER

Optional brackets are available

Factory-punched head holes for quick assembly

RoHS compliant

PRODUKTEGENSKABER

Artikelnummer: 508100

Materiale: Aluminium

A: 12.5mm

Hole Size (HS): 8mm

Height (H): 15mm

Length (L): 2000mm

Width (W): 35mm


Unit Weight: 0.9kg

YDERLIGERE PRODUKTOPLYSNINGER

Support kit and aluminum profile are sold separately.

When cable tray is used, we recommend installing a Flexbus Support at each extremity, in order to protect the Flexbus Conductor against potential sharp edges of the cable tray.

DIAGRAMS



ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på www.nvent.com og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden undladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.



Vores kraftfulde portefølje af mærker:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE