

FleXbus Extender Type 1 Flat and Pre-Drilled, 220 mm², 360 mm², 545 mm²

Data Solutions

KATALOGNUMMER

FLEXEXT50A1



CERTIFICERINGER



FUNKTIONER

Designed to extend the FleXbus Conductors

Delivered with the appropriate countersunk head screws, nuts and washers

Designed to be mounted on any nVent ERIFLEX DPCB Punched Plain Copper Busbar

PRODUKTEGENSKABER


Artikelnummer: 508110

Materiale: Copper

Conductor Size: 220 mm²; 360 mm²; 545 mm²

Unit Weight: 0.48kg

DIAGRAMS



ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på www.nvent.com og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden undladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.



Vores kraftfulde portefølje af mærker:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE