


MSP0 PDU, 2U, 60A(48A), 208V, 3P Delta, 6 CB, (9)C13, (9)4-in-1

Data Solutions

KATALOGNUMMER

EN6963



The Advantage Series Outlet Metered, Outlet Switched PDU family offers energy metering with advanced power and environmental monitoring options and remote outlet on/off switching. Comprehensive monitoring at the input phase, circuit breaker, and individual outlet levels offers advanced alerts of potential overloads. Billing-grade metering provides accurate power consumption data for energy use optimization. The hot-swappable network management controller features Gigabit and redundant ethernet communication with advanced support for external environmental sensors and rack security access solutions.

PRODUKTEGENSKABER

Produktfamilie: Enlogic

Product Type: Socket Strip

Stiktype: (9) C13/C15; (9) C13/C15/C19/C21

Circuit Breaker: 20 A

Farve: Black

Circuit Breaker Quantity: 6

Switched Outlets: Yes

Length: 87mm

Power Rating: 17.3 kVA

Interrupt Rating: 10kAIC

Number of Poles: 2

Input Voltage: 208V

Phase: 3 PH Delta

Output Voltage: 208VAC

Plug Type: IEC 60309 460P9 (IP44)

Nominal spænding: 208V

Removable Input Cable: No

Amperage (Derated Amperage): 60 A (48 A)

Rack Units: 2U

Type: Intelligent PDU

Finish: Struktur Pulvermaling

Metering Type: Outlet

Materiale: Stål

Højde: 87mm

Vægt: 9kg

Bredde: 444mm

Dybde: 269mm

Pakke mængde: 1

Input Cable Length: 1.8m

YDERLIGERE PRODUKTOPLYSNINGER

87 mm L x 444 mm W x 269 mm D, (269 mm D at CB)

ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer.

Vejledninger er tilgængelige på www.nvent.com og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden unladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.



Vores kraftfulde portefølje af mærker:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE