

# Socket Strip, Swiss

## Data Solutions

Modular, compact PDU with many function elements. Using a 1 U by 1 U aluminum chassis the PDU can easily be integrated in a rack with Swiss outlets.



### CERTIFICERINGER



### FUNKTIONER

Socket strips can be rotated through all four directions (in 90° increments) during installation

230 V, 10 A

In accordance with SEV.IEC 60884

Connecting cable 2 m with Swiss version plug

Socket strips Swiss version

Installation height 1 U

Horizontal or vertical mounting

### SPECIFIKATIONER

|                      |                      |
|----------------------|----------------------|
| <b>Length:</b>       | 438.5mm              |
| <b>Materiale:</b>    | Aluminium; Polyamide |
| <b>Farve:</b>        | Grey                 |
| <b>Product Type:</b> | Socket Strip         |

Table 1/2

| Katalognummer | Stiktype | Socket Quantity | Switched Outlets | Spænding AC | Pakke mængde | Dybde |
|---------------|----------|-----------------|------------------|-------------|--------------|-------|
| 60110-453     | Swiss    | 10              | No               | 230V        | 1            | 44mm  |
| 60110-454     | Swiss    | 9               | Yes              | 230V        | 1            | 44mm  |

Table 2/2

| Katalognummer | Finish   |
|---------------|----------|
| 60110-453     | Anodized |
| 60110-454     | Anodized |

## YDERLIGERE PRODUKTOPLYSNINGER

Please order bracket for vertical mounting separately.

## ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på [www.nvent.com](http://www.nvent.com) og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden unkladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.



Vores kraftfulde portefølje af mærker:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**