


Cable to Cable, Rail



nVent ERICO Cadweld applications for railway properties utilize the nVent ERICO Cadweld Plus F80 and the nVent ERICO Cadweld F80 welding material alloys. nVent ERICO Cadweld exothermically welded connections are engineered to provide a permanent, molecular bond that will not loosen or corrode, enabling connection of dissimilar materials. The connections are designed to perform for the life of the conductor and/or installation. The nVent ERICO Cadweld connection has a current carrying capacity equal to or greater than that of the conductor and will withstand repeated fault currents without failing during operation. Once completed, installers can clearly ensure quality by visually inspecting the new connection.

DIAGRAMS



FUNKTIONER

Forms a permanent, low resistance connection

Provides a molecular bond

nVent ERICO Cadweld Exothermic Connections are rated with the same current capacity as the conductor

Portable installation equipment with no external source of power required

Installers can be easily trained to make nVent ERICO Cadweld Exothermic Connections

Connections can be visually inspected

SPECIFIKATIONER

Table 1/5

| Katalognummer | Mold Family | Conductor 1 | Conductor 1 Outer Diameter, Nominal | Conductor 2 | Conductor 2 Outer Diameter, Nominal |
|---------------|-------------|-------------|-------------------------------------|-------------|-------------------------------------|
| | | | | | |

| | | | | | |
|------------|----|-------------------------------|---------|-------------------------------|---------|
| PB10PA1G1G | PA | #6 Solid | 4.11mm | #6 Solid | 4.11mm |
| SB02SS6 | SS | #6 Solid | 4.11mm | #6 Solid | 4.11mm |
| SB10SS1H1G | SS | #6 Concentric | 4.67mm | #6 Solid | 4.11mm |
| PB20TA2Q1H | TA | 4/0 Concentric | 13.41mm | #6 Concentric | 4.67mm |
| PB20TA2G1H | TA | 2/0 Concentric | 10.62mm | #6 Concentric | 4.67mm |
| PB10PC2C1H | PC | 1/0 Concentric | 9.47mm | #6 Concentric | 4.67mm |
| PB10SS2Q1H | SS | 4/0 Concentric | 13.41mm | #6 Concentric | 4.67mm |
| SB10SS1V3 | SS | #2 Concentric | 7.42mm | 3/16 Signal | 4.76mm |
| PB20TA1L2V | TA | #4 Concentric | 5.89mm | 250 kcmil Concentric | 14.61mm |
| PB20TA2V1L | TA | 250 kcmil Concentric | 14.61mm | #4 Concentric | 5.89mm |
| PB10SS2Q1L | SS | 4/0 Concentric | 13.41mm | #4 Concentric | 5.89mm |
| PB10SS1T | SS | #2 Solid | 6.53mm | #2 Solid | 6.53mm |
| PB20TA2Q1V | TA | 4/0 Concentric | 13.41mm | #2 Concentric | 7.42mm |
| SB10SS1V | SS | #2 Concentric | 7.42mm | #2 Concentric | 7.42mm |
| PB10SS1Y | SS | #1 Concentric | 8.43mm | #1 Concentric | 8.43mm |
| PB20PAY3Y3 | PA | 50 mm ² Concentric | 8.99mm | 50 mm ² Concentric | 8.99mm |
| PB20TAT2Y3 | TA | 10.0 mm Ground Wire | 10mm | 50 mm ² Concentric | 8.99mm |
| PB10SS2C | SS | 1/0 Concentric | 9.47mm | 1/0 Concentric | 9.47mm |
| PB10SS2Q2C | SS | 4/0 Concentric | 13.41mm | 1/0 Concentric | 9.47mm |
| PB20PP2CPS | PP | 1/0 Concentric | 9.47mm | B154A Plug | 12.7mm |

Table 2/5

| Katalognummer | Mold Family | Conductor 1 | Conductor 1 Outer Diameter, Nominal | Conductor 2 | Conductor 2 Outer Diameter, Nominal |
|---------------|-------------|----------------|-------------------------------------|----------------|-------------------------------------|
| PB20TA2C2C | TA | 1/0 Concentric | 9.47mm | 1/0 Concentric | 9.47mm |
| PB20TA2G2G | TA | 2/0 Concentric | 10.62mm | 2/0 Concentric | 10.62mm |
| PB10SS2G | SS | 2/0 Concentric | 10.62mm | 2/0 Concentric | 10.62mm |
| PB10SS2Q2G | SS | 4/0 Concentric | 13.41mm | 2/0 Concentric | 10.62mm |
| PB10PT2G2G | PT | 2/0 Concentric | 10.62mm | 2/0 Concentric | 10.62mm |
| PB99XB2Q2G | XB | 4/0 Concentric | 13.41mm | 2/0 Concentric | 10.62mm |
| PB20TA2Q2G | TA | 4/0 Concentric | 13.41mm | 2/0 Concentric | 10.62mm |
| PB20PG2G2G | PG | 2/0 Concentric | 10.62mm | 2/0 Concentric | 10.62mm |
| PB20PP2GPS | PP | 2/0 Concentric | 10.62mm | B154A Plug | 12.7mm |

| Katalognummer | Mold Family | Conductor 1 | Conductor 1 Outer Diameter, Nominal | Conductor 2 | Conductor 2 Outer Diameter, Nominal |
|---------------|-------------|----------------------|-------------------------------------|------------------|-------------------------------------|
| PB10SS2J | SS | 2/0 Ropelay | 12.19mm | 2/0 Ropelay | 12.19mm |
| PB20PPS6PS | PP | 3/0 Composite | 14.53mm | B154A Plug | 12.7mm |
| PB10PC2Q2S | PC | 4/0 Concentric | 13.41mm | 4/0 Ropelay | 15.49mm |
| PB20TAS5S5 | TA | 2/0 Composite | 13.36mm | 2/0 Composite | 13.36mm |
| PB20TA2Q2Q | TA | 4/0 Concentric | 13.41mm | 4/0 Concentric | 13.41mm |
| PB10SS2Q | SS | 4/0 Concentric | 13.41mm | 4/0 Concentric | 13.41mm |
| PB20TA2Q4R | TA | 4/0 Concentric | 13.41mm | 1100/#24 Ropelay | 22.4mm |
| PB99XB2Q2Q | XB | 4/0 Concentric | 13.41mm | 4/0 Concentric | 13.41mm |
| PB13SV2Q | SV | 4/0 Concentric | 13.41mm | 4/0 Concentric | 13.41mm |
| PB10SS2V2Q | SS | 250 kcmil Concentric | 14.61mm | 4/0 Concentric | 13.41mm |
| PB10SS2S2Q | SS | 4/0 Ropelay | 15.49mm | 4/0 Concentric | 13.41mm |

Table 3/5

| Katalognummer | Mold Family | Conductor 1 | Conductor 1 Outer Diameter, Nominal | Conductor 2 | Conductor 2 Outer Diameter, Nominal |
|---------------|-------------|----------------------|-------------------------------------|----------------------|-------------------------------------|
| PB10SS2V | SS | 250 kcmil Concentric | 14.61mm | 250 kcmil Concentric | 14.61mm |
| PB20TA2V2V | TA | 250 kcmil Concentric | 14.61mm | 250 kcmil Concentric | 14.61mm |
| PB10SSS6 | SS | 3/0 Composite | 14.53mm | 3/0 Composite | 14.53mm |
| PB99XB2V2V | XB | 250 kcmil Concentric | 14.61mm | 250 kcmil Concentric | 14.61mm |
| PB10PTS6S6 | PT | 3/0 Composite | 14.53mm | 3/0 Composite | 14.53mm |
| PB99XB2V2VM | XB | 250 kcmil Concentric | 14.61mm | 250 kcmil Concentric | 14.61mm |
| PB10SS2W2V | SS | 250 kcmil Ropelay | 19.05mm | 250 kcmil Concentric | 14.61mm |
| PB10SS2S | SS | 4/0 Ropelay | 15.49mm | 4/0 Ropelay | 15.49mm |
| PB10SS2W3DC | SS | 250 kcmil Ropelay | 19.05mm | 350 kcmil Compact | 15.88mm |
| PB10SSS7 | SS | 4/0 Composite | 16.66mm | 4/0 Composite | 16.66mm |
| PB10SS3SS7 | SS | 500 kcmil Ropelay | 26.42mm | 4/0 Composite | 16.66mm |
| PB10SS4K2W | SS | 650/#24 Ropelay | 16.92mm | 250 kcmil Ropelay | 19.05mm |
| PB10SS3S3D | SS | 500 kcmil Ropelay | 26.42mm | 350 kcmil Concentric | 17.3mm |

| Katalognummer | Mold Family | Conductor 1 | Conductor 1 Outer Diameter, Nominal | Conductor 2 | Conductor 2 Outer Diameter, Nominal |
|---------------|-------------|----------------------|-------------------------------------|----------------------|-------------------------------------|
| PB10SS3Q3D | SS | 500 kcmil Concentric | 20.65mm | 350 kcmil Concentric | 17.3mm |
| PB10SS3D | SS | 350 kcmil Concentric | 17.3mm | 350 kcmil Concentric | 17.3mm |
| PB10SS3S3QC | SS | 500 kcmil Ropelay | 26.42mm | 500 kcmil Compact | 18.62mm |
| PB20TA3QC3QC | TA | 500 kcmil Compact | 18.62mm | 500 kcmil Compact | 18.62mm |
| PB10SS3QC3S | SS | 500 kcmil Compact | 18.62mm | 500 kcmil Ropelay | 26.42mm |
| PB50PC3S2W | PC | 500 kcmil Ropelay | 26.42mm | 250 kcmil Ropelay | 19.05mm |
| PB50PC5A2W | PC | 1000 kcmil Ropelay | 33.78mm | 250 kcmil Ropelay | 19.05mm |

Table 4/5

| Katalognummer | Mold Family | Conductor 1 | Conductor 1 Outer Diameter, Nominal | Conductor 2 | Conductor 2 Outer Diameter, Nominal |
|---------------|-------------|-----------------------|-------------------------------------|-----------------------|-------------------------------------|
| PB20TA2W3S | TA | 250 kcmil Ropelay | 19.05mm | 500 kcmil Ropelay | 26.42mm |
| PB10SS2W | SS | 250 kcmil Ropelay | 19.05mm | 250 kcmil Ropelay | 19.05mm |
| PB50SS5A2W | SS | 1000 kcmil Ropelay | 33.78mm | 250 kcmil Ropelay | 19.05mm |
| PB10SS2W3S | SS | 250 kcmil Ropelay | 19.05mm | 500 kcmil Ropelay | 26.42mm |
| PB10SS3S4M | SS | 500 kcmil Ropelay | 26.42mm | 775 kcmil/#24 Ropelay | 19.02mm |
| PB10SS3B3S | SS | 300 kcmil Ropelay | 20.32mm | 500 kcmil Ropelay | 26.42mm |
| PB20TA3Q3Q | TA | 500 kcmil Concentric | 20.65mm | 500 kcmil Concentric | 20.65mm |
| PB63TA6H3Q | TA | 2000 kcmil Concentric | 40.94mm | 500 kcmil Concentric | 20.65mm |
| PB80PG5T3Q | PG | 1500 kcmil Concentric | 35.86mm | 500 kcmil Concentric | 20.65mm |
| PB10SS3Q | SS | 500 kcmil Concentric | 20.65mm | 500 kcmil Concentric | 20.65mm |
| PB60TA4Y3Q | TA | 1000 kcmil Concentric | 29.26mm | 500 kcmil Concentric | 20.65mm |
| PB10SS3S3Q | SS | 500 kcmil Ropelay | 26.42mm | 500 kcmil Concentric | 20.65mm |
| PB60TA3Q4Y | TA | 500 kcmil Concentric | 20.65mm | 1000 kcmil Concentric | 29.26mm |

| Katalognummer | Mold Family | Conductor 1 | Conductor 1 Outer Diameter, Nominal | Conductor 2 | Conductor 2 Outer Diameter, Nominal |
|---------------|-------------|----------------------|-------------------------------------|-------------------|-------------------------------------|
| PB10SS4R | SS | 1100/#24 Ropelay | 22.4mm | 1100/#24 Ropelay | 22.4mm |
| PB20TA4R4R | TA | 1100/#24 Ropelay | 22.4mm | 1100/#24 Ropelay | 22.4mm |
| PB10SS3S3F | SS | 500 kcmil Ropelay | 26.42mm | 350 kcmil Ropelay | 22.35mm |
| PB50SS4L4T | SS | 750 kcmil Concentric | 25.35mm | 1325/#24 Ropelay | 24.94mm |
| PB10SS3S4T | SS | 500 kcmil Ropelay | 26.42mm | 1325/#24 Ropelay | 24.94mm |
| PB31TA4T4T | TA | 1325/#24 Ropelay | 24.94mm | 1325/#24 Ropelay | 24.94mm |
| PB50SS4L3S | SS | 750 kcmil Concentric | 25.35mm | 500 kcmil Ropelay | 26.42mm |

Table 5/5

| Katalognummer | Mold Family | Conductor 1 | Conductor 1 Outer Diameter, Nominal | Conductor 2 | Conductor 2 Outer Diameter, Nominal |
|---------------|-------------|-----------------------|-------------------------------------|-----------------------|-------------------------------------|
| PB10SS4L | SS | 750 kcmil Concentric | 25.35mm | 750 kcmil Concentric | 25.35mm |
| PB80PA5T4L | PA | 1500 kcmil Concentric | 35.86mm | 750 kcmil Concentric | 25.35mm |
| PB20TA3S3S | TA | 500 kcmil Ropelay | 26.42mm | 500 kcmil Ropelay | 26.42mm |
| PB10SS3S | SS | 500 kcmil Ropelay | 26.42mm | 500 kcmil Ropelay | 26.42mm |
| PB50SS3S4N | SS | 500 kcmil Ropelay | 26.42mm | 750 kcmil Ropelay | 29.34mm |
| PB10SS3S4X | SS | 500 kcmil Ropelay | 26.42mm | 1600/#24 Ropelay | 27.18mm |
| PB60TA4N3S | TA | 750 kcmil Ropelay | 29.34mm | 500 kcmil Ropelay | 26.42mm |
| PB50PC3S5A | PC | 500 kcmil Ropelay | 26.42mm | 1000 kcmil Ropelay | 33.78mm |
| PB50SS3S5A | SS | 500 kcmil Ropelay | 26.42mm | 1000 kcmil Ropelay | 33.78mm |
| PB50SS3S4Y | SS | 500 kcmil Ropelay | 26.42mm | 1000 kcmil Concentric | 29.26mm |
| PB60TA4X4X | TA | 1600/#24 Ropelay | 27.18mm | 1600/#24 Ropelay | 27.18mm |
| PB50SS4Y | SS | 1000 kcmil Concentric | 29.26mm | 1000 kcmil Concentric | 29.26mm |
| PB50SS4N | SS | 750 kcmil Ropelay | 29.34mm | 750 kcmil Ropelay | 29.34mm |
| PB50PC5A5A | PC | 1000 kcmil Ropelay | 33.78mm | 1000 kcmil Ropelay | 33.78mm |
| PB50SS5A | SS | 1000 kcmil Ropelay | 33.78mm | 1000 kcmil Ropelay | 33.78mm |
| PB53SS6H | SS | 2000 kcmil Concentric | 40.94mm | 2000 kcmil Concentric | 40.94mm |

YDERLIGERE PRODUKTOPLYSNINGER

For applications such as computer room, tunnel or other low-ventilation areas, specify a smokeless nVent ERICO Cadweld Exolon mold. Add an XL prefix to the standard mold part number when ordering (for example, a PB10GR162G becomes XLPB10GR162G). Similarly, nVent ERICO Cadweld Exolon welding material is also designated by the XL prefix (for example, PB90 becomes XLPB90).

A gap between conductors may be required. See mold tag for more information.

| XXXX-XX-XX-XX-L-M-W | | |
|---------------------|------------------|---|
| XXXX | Price Key | |
| XX | Mold Family | |
| XX | Conductor Code 1 | |
| XX | Conductor Code 2 | |
| L* | Split Crucible | Crucible section is split on molds designed with horizontal opening for easier cleaning |
| M* | Mold Only | |
| W* | Wear Plates | Reduce mechanical abrasion of molds at cable entry points |

* Empty if none

ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på www.nvent.com og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden undladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Vores kraftfulde portefølje af mærker:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE