

# Non-Insulated Solid Conductor



## FUNKTIONER

Solid cable for a variety of applications

Available in smaller spool sizes for convenience

LPA and LPC parts are used for lightning protection system downconductor or grounding applications

## SPECIFIKATIONER

Table 1/2

Katalognummer	Artikelnummer	Materiale	Finish	Conductor Size	Cross Section	Diameter (Ø)
ASC0850	711530	Aluminium	Bare	8 mm Solid	50.3mm <sup>2</sup>	8 mm
RSCC8100	197860	Stål	Hot-Dip Galvanized	1/0 Solid	50.3mm <sup>2</sup>	8 mm
RSCC2SS830	197685	Stainless Steel 304 (EN 1.4301)	Bare	1/0 Solid	50.3mm <sup>2</sup>	8 mm
RC-ET-8	198210	Copper	Tinned	1/0 Solid	50.2mm <sup>2</sup>	8 mm
RC-EC-8	198160	Copper	Bare	1/0 Solid	50.2mm <sup>2</sup>	8 mm

Table 2/2

Katalognummer	Artikelnummer	Length (L)	Unit Weight	Complies With
ASC0850	711530	50m	0.14 kg	
RSCC8100	197860	125m	0.4 kg	
RSCC2SS830	197685	30m	0.4 kg	
RC-ET-8	198210	100m	0.45 kg	


Katalognummer	Artikelnummer	Length (L)	Unit Weight	Complies With
RC-EC-8	198160	100m	0.45 kg	IEC® EN 62561-2

## YDERLIGERE PRODUKTOPLYSNINGER

Unit weight is per foot (0.3048 m).

Cut-to-order (CTO) lengths are available for an additional charge.

## DIAGRAMS



## ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på [www.nvent.com](http://www.nvent.com) og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden undladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.

### North America

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical  
Support

### Europe

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

### Europe

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

### APAC

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Vores kraftfulde portefølje af mærker:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**