

Ejection Stop Kit



CERTIFICATIONS



FEATURES

Holds nVent ERIFLEX Flexibar laminates in place while punch is raised

Pressure plates notched to apply pressure to laminates without damaging the insulation

Punch tip remains visible when kit is attached to puncher

RoHS compliant

SPECIFICATIONS

Table 1/1

| Catalog Number | Article Number | Product | Material | Punch Size | Unit Weight |
|----------------|----------------|------------------------------------|-------------------|---|-------------|
| EJECSTOP18-20S | 545896 | Replacement Ejection Stop | Elastomere | 18.0 mm, 20.0 mm | 0.06 kg |
| EJECSTOP6-14S | 545895 | Replacement Ejection Stop | Elastomere | 6.5 mm, 9.0 mm, 11.0 mm, 14.0 mm, 5/16", 3/8", 17/32" | 0.07 kg |
| EJECSTOP18-20L | 545894 | Ejection Stop with Pressure Plates | Steel, Elastomere | 18.0 mm, 20.0 mm | 0.28 kg |

| Catalog Number | Article Number | Product | Material | Punch Size | Unit Weight |
|----------------|----------------|---|-------------------|---|-------------|
| EJECSTOP6-14L | 545893 | Ejection Stop with Pressure Plates and Washer | Steel, Elastomere | 6.5 mm, 9.0 mm, 11.0 mm, 14.0 mm, 5/16", 3/8", 17/32" | 0.55 kg |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE