We connect and protect

Compression Lugs 1.00 Hole-to-Hole C/C, Fits #2 Cable, Brown, Copper

Data Solutions

CATALOG NUMBER

DGCL22

The Compression Lugs terminate copper or tinned-copper conductors for connection to busbars, cabinets, racks, and cable runway. They are color-coded by conductor size. Installation of the Compression Lugs requires two screws (not included).

FEATURES

The Compression Lugs terminate copper or tinned-copper conductors for connection to busbars, cabinets, racks, and cable runway

They are color-coded by conductor size. Installation of the Compression Lugs requires two screws (not included)

PRODUCT ATTRIBUTES

Article Number: 17255

Material: Copper

Finish: Electroplated; Tinned

Thickness: 3.5mm

Cable Size: #2

Required Screw Size: 3/8

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2026 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.