We connect and protect

InterSafe Data Interface Port for ControlNet

InterSafe Data Interface Port allows programming access to devices inside without opening the enclosure door, reducing the risk of exposing to energized components. Many configurations are standard and ready-to-use to meet various applications and programming requirements.

FEATURES

- Steel and Stainless Steel doors are welded and ground
- Back plate is aluminum
- All standard configurations include a GFCI or standard duplex receptacle with a 5-A circuit breaker for added safety
- Door gasket (between the door and plate assemblies) and plate gasket (between the plate assembly and the enclosure) together provide a tight seal
- Template provided for accurate enclosure cutout dimensions
- Quarter-turn latch with screwdriver slot and padlock hasp on all steel and stainless steel door models for convenience and security
- Quarter-turn latch with screwdriver slot on polycarbonate models

SPECIFICATIONS

Table 1/1

Catalog Number	Article Number	Material	Finish	Color	Thickness	Configuration
HDP5CNCC	16175	Polycarbonate	Smooth Matte		1.5mm	120 VAC Duplex Receptacle, Shielded RJ45, 5-amp Circuit Breaker
HGF5CNSS	15942	Stainless Steel 304	Brushed		1.5mm	120 VAC GFCI Receptacle, Shielded RJ45, 5-amp Circuit Breaker
HDP5CN	14934	Mild Steel	Powder Coated	Black	1.5mm	120 VAC Duplex Receptacle, Shielded RJ45, 5-amp Circuit Breaker
HDP5CNSS	15928	Stainless Steel 304	Brushed		1.5mm	120 VAC Duplex Receptacle, Shielded RJ45, 5-amp Circuit Breaker
HGF5CNCC	16191	Polycarbonate	Smooth Matte		1.5mm	120 VAC GFCI Receptacle, Shielded RJ45, 5-amp Circuit Breaker
HGF5CN	14786	Mild Steel	Powder Coated	Black	1.5mm	120 VAC GFCI Receptacle, Shielded RJ45, 5-amp Circuit Breaker

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2026 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.