


# FleXbus Aluminum Perforated Profile

## Data Solutions

### CATALOG NUMBER

**FLEXALPROF2M**



### CERTIFICATIONS



### FEATURES

Optional brackets are available

Factory-punched head holes for quick assembly

RoHS compliant

### PRODUCT ATTRIBUTES

Article Number: 508100

Material: Aluminum

A: 0.49in

Hole Size (HS): 0.32in

Height (H): 0.59in

Length (L): 78.7in

Width (W): 1.38in

Unit Weight: 1.98lb

## ADDITIONAL PRODUCT DETAILS


---

Support kit and aluminum profile are sold separately.

When cable tray is used, we recommend installing a Flexbus Support at each extremity, in order to protect the Flexbus Conductor against potential sharp edges of the cable tray.

## DIAGRAMS

---



## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**