

# Compression Lugs 0.625 Hole-to-Hole C/C, Fits #2 Cable, Brown, Copper

## Data Solutions

### CATALOG NUMBER

**DGCL21**



The Compression Lugs terminate copper or tinned-copper conductors for connection to busbars, cabinets, racks, and cable runway. They are color-coded by conductor size. Installation of the Compression Lugs requires two screws (not included).

### FEATURES

The Compression Lugs terminate copper or tinned-copper conductors for connection to busbars, cabinets, racks, and cable runway

They are color-coded by conductor size. Installation of the Compression Lugs requires two screws (not included)

### PRODUCT ATTRIBUTES

Article Number: 17254

Material: Copper

Finish: Electroplated; Tinned

Thickness: 0.14in

Cable Size: #2

On-Center Dimension Between Holes: 0.625in

Required Screw Size: 1/4

Weight: 1lb

## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**