

Seismic Free-Stand DA Cabinet Type 12, 72x36x46, Lt Gray, Steel

Data Solutions

NÚMERO DE CATÁLOGO

D723646SDA

Ideal where front or front and rear access is required. These enclosures have sturdy unibody construction with 19-inch rack angles to support equipment. These enclosures are ideal for housing and protecting networking and communications from dust, liquid, and seismic events. 36-inch wide models include integral, vertical cable management that supports copper and fiber networking cables.



NORMAS DA INDÚSTRIA

UL 508A Listed; Type 4; File No. E61997
 cUL Listed per CSA C22.2 No. 94; Type 4; File No. E61997
 NEMA/EEMAC Type 4
 E.I.A. RS310-D
 CSA, File No. 42186, Type 4
 IEC 60529, IP55
 OSPHD Pre Approved OPM -0248-13
 NEBS-Telecordia GR-63-CORE Zone 4: Tested with 1000 lb. of equipment installed
 Meets California Building Code (CBC) requirements

CARACTERÍSTICAS

Reinforced stainless steel construction protects networking/communication equipment from dust, liquid, and seismic activity

Six seismic bottom-mounting plates made of painted plated steel for 5/8-inch diameter anchors

Lifting eyes installed for ease of handling

Rack angles included are infinitely adjustable from front-to-rear supporting multiple networking/communication equipment configurations

36-inch wide models include integral, vertical, RU-aligned fingers for supporting copper and fiber networking cables

AC models available for heat management

CARACTERÍSTICAS DO PRODUTO

Número do artigo: 35447

Altura: 1834mm

Largura: 918mm

Profundidade: 1173mm

Material: Aço Macio

Acabamento: Pintura electrostática com Acabamento Texturado

Cor: Light Gray

Código de cor: RAL 7035

Espessura: 2.66mm

Rack Units: 35U

AVISO

Os produtos nVent devem ser instalados e utilizados apenas conforme indicado nas fichas de instrução do produto e materiais de treinamento da nVent. As fichas de instrução estão disponíveis em www.nVent.com e com nossos representantes de atendimento ao cliente nVent. A instalação inadequada, uso incorreto, aplicação incorreta ou outra falha qualquer em seguir completamente as instruções e avisos da nVent podem levar ao mau funcionamento do produto, danos à propriedade, lesões corporais graves e morte, e/ou anular sua garantia.



O nosso forte portefólio de marcas:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE