

FleXbus Shear

Data Solutions

NUMĂR DE CATALOG

FLEXSHEAR



CARACTERISTICI

Shear is used to cut the FleXbus Conductor over length

Favorable lever ratio and optimized cutting edge geometry require less effort

Adjustable bolted joint, self-retaining screw

Precision-ground, hardened blades

Allows for a clean, smooth cut without causing crushing or deformation

Guard provides added safety

High-grade special tool steel, forged, oil-hardened

ATRIBUTE PRODUS

Article Number: 508173

Material: Oțel

Unit Weight: 0.32kg

AVERTIZARE

Produsele nVent trebuie instalate și utilizate numai așa cum este indicat în fișele de instrucțiuni și materialele de formare ale nVent. Fișele de instrucțiuni sunt disponibile pe www.nvent.com și de la reprezentantul dvs. de servicii clienți nVent. O instalare incorectă, o utilizare abuzivă, o aplicare greșită sau orice altă lipsă de respectare completă a instrucțiunilor și avertismentelor nVent poate duce la defectarea produsului, la deteriorarea proprietății, la răni corporale grave și moarte

și/sau poate anula garanția dvs.



Portofoliul nostru puternic de mărci:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE