



# Data Solutions

# EA9101

**Alarm Beacon sensors are accessories attached to nVent Enlogic iPDUs, which are designed to create a visible alarm notification for an alert condition (or other userdefined situation) in an effort to notify IT personnel quickly and efficiently. They provide information via Web UI, SNMP, CLI/SSH interfaces.**

**These devices produce visual alerts that direct users' attention to a designated area**

**The beacon is attached to an iPDU's sensor port 1 or port 2, and it flashes a red LED for 0.5 secs ON/0.5 secs OFF rhythmically until the issue is fixed or warnings are resolved**

**A standard RJ-45 connector may be used to extend the Alarm Beacon up to a distance of 30.5 meters**

?????: ???

?: 300mm

**?: 98mm**

????: 1

????: RJ45

????: Enlogic

??????: ?

?: 0.5kg

**?: 100mm**

??????

**Includes: (5) Cable Ties, (1) RJ45 Quick Disconnect Coupler, (5) Adhesive Backed Mounts, (1) 1.8m standard ethernet extension cable**

??

???? nVent ????????????????? nVent ??????? www.nvent.com ??????????? nVent ????????????????????????????????????? nVent  
 ?????????????????????????????????????????/????????????



?????????:

CADDY   ERICO   HOFFMAN   ILSCO   SCHROFF   TRACHTE