

PDU, 0U, 60A(48A)NA/63A Int, 380-415V, 3P Wye, 12 CB (18)C13 (18)4-in-1

Data Solutions

???

EB09JA

The Basic PDU is a cost-effective, reliable power distribution solution. Premium hydraulic-magnetic circuit breakers operate consistently in high-temperature environments. The Basic PDU offers advanced features, such as color-coded locking IEC outlets, a slim chassis design, and toolless mounting backed by a 5-year hassle-free warranty.

??

Black Powder Coated Chassis

IEC 62368 listed. RoHS, and REACH compliant. See drawing for additional information.

????

????: Enlogic

?: ??? PDU

????: ??

????: (18) C13/C15; (18) C13/C15/C19/C21

????: 36

?: ??

????: ?

????: 1800mm

?: 20 A?1 ??Hy-MagA

????: 34.6 kVA ??; 43.5 kVA ??

?????: 12

?????: 230VAC

????: 415V

?????: 36

???/????: ?

?????????: 60 A (48 A) ??; 63 A ??

????: 208 – 230VAC

????: 0U

????: IEC 60309 560P6/563P6

????: ?

????????: ?

?: ?

?: ????

?: 965mm

?: 114mm

?: 75mm

????: 1

?????: 1.8m

??????

Warranty : nVent Enlogic branded equipment provided shall be free from manufacturing defects for a period of five (5) years from the invoice date to the original purchaser.

??

???? nVent ?????????????????? nVent ??????? www.nvent.com ??????????? nVent ??? nVent
??



???????????:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE